



Rotalec

ROTALEC PRESENTS: THE BANNER SC22-3 SAFETY CONTROLLER **Machine Safety**

Rotalec is very excited to introduce the SC22-3 Safety Controller! The Safety Controller has fully configurable inputs and outputs to manage multiple safety related functions all on one device. It was developed to simplify the process of interfacing safety and safeguarding devices.



Features

- PCI software included with the SC22-3 Safety Controller; No licensing or additional charges.
- 22 Inputs for safety and non-safety input devices
- 3 dual channel Safety outputs (24V dc @ 0.75A) with selectable ON- and OFF-delay
- 10 Status outputs track input and output status, mute status, lockout, fault conditions and reset needed
- Configurations are transferable to multiple SC22-3 Controllers and can be e-mailed as attachments
- Complies with Safety Integrity Level (SIL) 3 per IEC 62061 and IEC 61508, and Category 4 Performance Level “e” per ISO 13849-1.
- Live display and fault log provide “real-time” status information and historically track faults
- Wiring diagram, Ladder Logic diagram, and Configuration Summary can be printed or exported as .pdf or .dxf files

Applications

- Robotic Welding Cells
- Power Presses
- Lean Manufacturing Cells
- Global/Local Emergency Stop functions
- Bypassing, Muting, and Enabling Device/Pendent monitoring
- Specialized machinery